

MV53X Datasheet

Overview

This MV53X is a new member of the third-generation MV smart camera family. It is an outdoor bullet camera that combines advanced analytics and 12-37° varifocal FoV. This camera provides long distance monitoring and security for a variety of deployments including parking lots, warehouses, security checkpoints and more.



Product Highlights

- Varifocal lens bullet camera with 1/1.8" 8.41MP Image Sensor
 - Bullet form factor with 12-37° horizontal FoV
 - More detailed information with up to 4K resolution
 - Low bandwidth Consumption for recording and streaming using Smartcodec encoding
 - Guaranteed days of video with [Smart Retention](#)
 - Night vision with IR illumination up to 50m (164 ft)
 - Intelligent motion indexing with search engine
 - Built-in search tools like motion search, motion recap, motion heatmaps and Attribute Search.
 - Machine-learning capability for intelligent object detection
 - Secure video access to ensure privacy with end-to-end encryption
 - Cloud-augmented edge storage for minimal bandwidth consumption
 - Built-in automatic security with secure boot and encrypted storage
 - Suitable for deployments of all sizes, from 100 to 10,000 cameras
 - NDAA Compliant
-

- Built-in analytics like Line Crossing, Area Occupancy, MV sense and Custom Computer-Vision capabilities

MV53X Camera Specifications

Category	Specifications
Camera	<ul style="list-style-type: none"> • 1/1.8" 8.41MP (3840x2160) progressive CMOS image sensor • 12-37° Varifocal Lens • 1TB high-endurance solid-state storage • 12.5-38 mm focal length range • f/2.05 - f/2.2 aperture range • Auto and Manual Focus Controls • Auto day/night capable • Built in IR-illuminators, effective up to 50m (149 ft)
Video	<ul style="list-style-type: none"> • 4K video recording (3840x2160) with H.264 Smart Codec encoding, up to 15fps • 4MP (2560 x 1440) with H.264 Smart Codec encoding, up to 24fps • 1080p (1920x1080) with H.264 Smart Codec encoding, up to 24fps • High dynamic range (HDR) • Cloud augmented edge storage (locally stored video, metadata in the cloud) • Optimized retention settings (scheduling, motion-based) for variable retention • Direct live streaming with no client software (native browser playback)*** • Stream video anywhere with automatic cloud proxy
DORI Specifications (Maximum Resolution)	Unzoomed
	<ul style="list-style-type: none"> • Detect (25 ppm/ 8 ppf) <ul style="list-style-type: none"> ◦ 246.5 m / 808.7 ft • Observe (63 ppm/ 19 ppf) <ul style="list-style-type: none"> ◦ 97.8 m / 320.8 ft • Recognize (125 ppm/ 38 ppf) <ul style="list-style-type: none"> ◦ 49.3 m / 161.7 ft • Identify (250 ppm/ 76 ppf) <ul style="list-style-type: none"> ◦ 24.7 m / 81.0 ft
	Fully Zoomed
	<ul style="list-style-type: none"> • Detect (25 ppm/ 8 ppf) <ul style="list-style-type: none"> ◦ 778.8 m / 2555.1 ft • Observe (63 ppm/ 19 ppf) <ul style="list-style-type: none"> ◦ 309.1 m / 1014.1 ft • Recognize (125 ppm/ 38 ppf) <ul style="list-style-type: none"> ◦ 155.8 m / 511.2 ft • Identify (250 ppm/ 76 ppf) <ul style="list-style-type: none"> ◦ 77.9 m / 255.6 ft
Data and Network Security	<ul style="list-style-type: none"> • Full disk encryption (AES 256-bit) • Automatically purchased and provisioned TLS certificates (publicly-signed) • Management encryption and two-factor authentication

Networking and Wireless	<ul style="list-style-type: none"> • 1x 10/100/1000 Base-T Ethernet (RJ45) • DSCP traffic marking
Power	<ul style="list-style-type: none"> • Power Consumption: up to 30W via 802.3at PoE <ul style="list-style-type: none"> ◦ PoE+ required for operation
Environment	Temperature: -40°C - 50°C (-40°F - 122°F)
In The Box	<ul style="list-style-type: none"> • Quick start & installation guide • MV camera hardware • Wall mounting kit • Security and installation wrenches
Physical Characteristics	<ul style="list-style-type: none"> • Female RJ45 Ethernet connector • Multicolor, multifunction status LED, microphone cut-off switch • Reset Button
Mounting Options	<ul style="list-style-type: none"> • Wall/ceiling • Pole/corner with accessories
Ratings	<ul style="list-style-type: none"> • IK10+ vandal-resistance • IP67 weather-proofing
Warranty	5 year hardware warranty with advanced replacement
Hardware	MV53X-HW Varifocal lens outdoor bullet camera with 1TB storage
Licensing	<ul style="list-style-type: none"> • LIC-MV-XYR: Meraki MV Enterprise license (X = 1, 3, 5, 7, 10 years) • [Optional] LIC-MV-SEN-XYR: Meraki MV Sense license (X = 1, 3, 5, 7, 10 years) • [Optional] LIC-MV-CA30-XY: MV Cloud Archive license (X = 1, 3, 5 years) • [Optional] LIC-MV-CA90-XY: MV Cloud Archive license (X = 1, 3, 5 years) • [Optional] LIC-MV-CA180-XY: MV Cloud Archive license (X = 1, 3, 5 years) • [Optional] LIC-MV-CA365-XY: MV Cloud Archive license (X = 1, 3, 5 years)
Compatible Accessories	<ul style="list-style-type: none"> • MA-MNT-MV-28: Pole mount • MA-MNT-MV-58: Conduit back box • MA-MNT-MV-88: Corner Mount